

Classic Globe 200 LED 3000K


The Classic series is an old favourite of our assortment. Ideal in most areas where functionality and timeless design are the key words. Classic is available in different combinations and are also available with a grey or a brown glazed base as option.

EAN / GTIN	7312906046406
E-number	7503690
Article no.	6046-840-10
Type designation	51765/LED

Specification

Base colourWhite (NCS \$ 1000-N)GlassShiny opal glassGlass thread (mm)123,5 mmGlass gasketSiliconeWeight1,59 kgDiameter (mm)200Height (mm)216Lamp holderLEDLight sourceLED module, 10W **Effect10WLumen, light source1000lmLumen, luminarire794Colour temperature3000KMacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable inletBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic GlobeDesignIfö Electric	Material	Porcelain
Glass thread (mm)123,5 mmGlass gasketSiliconeWeight1,59 kgDiameter (mm)200Height (mm)216Lamp holderLEDLight sourceLD module, 10W **Effect10WLumen, light source1000lmLumen, light source3000KMacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Base colour	White (NCS S 1000-N)
Glass gasketSiliconeWeight1,59 kgDiameter (mm)200Height (mm)216Lamp holderLEDLight sourceLED module, 10W **Effect10WLumen, light source1000lmLumen, luminarire794Colour temperature3000KMacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Glass	Shiny opal glass
Weight1,59 kgDiameter (mm)200Height (mm)216Lamp holderLEDLight sourceLED module, 10W **Effect10WLumen, light source1000lmLumen, luminarire794Colour temperature3000KMacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Glass thread (mm)	123,5 mm
Diameter (mm)200Height (mm)216Lamp holderLEDLight sourceLED module, 10W **Effect10WLumen, light source1000lmLumen, luminarire794Colour temperature3000KMacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Glass gasket	Silicone
Height (mm)216Lamp holderLEDLight sourceLED module, 10W **Effect10WLumen, light source1000lmLumen, luminarire794Colour temperature3000KMacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable inletBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Weight	1,59 kg
Lamp holderLEDLight sourceLED module, 10W **Effect10WLumen, light source1000lmLumen, luminarire794Colour temperature3000KMacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIKO2Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Diameter (mm)	200
Light sourceLED module, 10W **Effect10WLumen, light source1000lmLumen, luminarire794Colour temperature3000KMacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIKO2Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesConnectionTerminal blockFamilyClassic Globe	Height (mm)	216
Effect10WLumen, light source1000lmLumen, luminarire794Colour temperature3000KMacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Lamp holder	LED
Lumen, light source1000lmLumen, luminarire794Colour temperature3000KMacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Light source	LED module, 10W **
Lumen, luminarire794Colour temperature3000KMacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Effect	10W
Colour temperature3000KMacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Lumen, light source	1000lm
MacAdam3Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Lumen, luminarire	794
Life spanL80/B10: 47 000 hRaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIKO2Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Colour temperature	3000K
RaMin 90Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	MacAdam	3
Rated voltage230VDimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Life span	L80/B10: 47 000 h
DimmableRC modeIP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Ra	Min 90
IP classIP44Insulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Rated voltage	230V
Insulation classIInsulation classIEnergy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Dimmable	RC mode
Energy classFIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	IP class	IP44
IntersectionIKO2IK classIKO2Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Insulation class	1
Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Energy class	F
InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	IK class	IK02
CC measurement (mm)60-66, 70Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Та	-30 - +25
Knock out opening4Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Installation	Ceiling/wall
Cable inletBottom inletCable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	CC measurement (mm)	60-66, 70
Cable glandsBottom inletCable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Knock out opening	4
Cable area, maxMax 3 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Cable inlet	Bottom inlet
BridgingYesSurface mounted cableYesConnectionTerminal blockFamilyClassic Globe	Cable glands	Bottom inlet
Surface mounted cable Yes Connection Terminal block Family Classic Globe	Cable area, max	Max 3 x 2,5 mm2
ConnectionTerminal blockFamilyClassic Globe	Bridging	Yes
Family Classic Globe	Surface mounted cable	Yes
	Connection	Terminal block
Design Ifö Electric	Family	Classic Globe
	Design	Ifö Electric





Maintenance

Disconnect the power to the luminaire. Unscrew the glass and clean it. Do not use detergents that contain solvents. Replace light source if necessary. Check the gasket and replace it if necessary. Screw the shade back on.

Spare parts

Shade globe Ø 200 mm shiny opal, Article no.: 1-6141 Gasket silicone for thread 123,5 mm, Article no.: 02789 LED module 10W 3000K, Article no.: 1-54056-930

** The device must under no circumstances be connected to the same phase as a magnetic ballast or other older fluorescent luminaires as these luminaires can generate overvoltage transients outside of EU regulatory standards when switched off or on. The luminaire can permanently damage or completely cease to function when connected.

If the luminaire is modified the person responsible for the modification shall be considered manufacturer. Subject to errors in text. We reserve the right to change the technical specifications (without notice).