

# Opus 120/200

Open 120 is an elegant cylindrical shaped light fitting. Its timeless design is suitable for wall or celing installation, both indoors and outdoord. Opus 120 is available with a matt opal or clear glass shade.


EAN / GTIN	7312907244306
E-number	7530840
Article no.	7244-510-10
Type designation	52760
Norwegian El-number	3032253
Finnish S-number	4112866



## Specification

Base colourWhite (NCS S 1000-N)GlassClear glassGlass thread (mm)99 mmGlass gasketSiliconeWeight1,4 kgDiameter (mm)116Height (mm)204Lamp holderE27Light sourceE27, max 60W (not included)EffectMax 60WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpusDesignDuoform	Material	Porcelain
Glass Glass sthread (mm)99 mmGlass gasketSiliconeWeight1,4 kgDiameter (mm)116Height (mm)204Lamp holderE27Light sourceE27, max 60W (not included)EffectMax 60WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Base colour	White (NCS S 1000-N)
Glass gasketSiliconeWeight1,4 kgDiameter (mm)116Height (mm)204Lamp holderE27Light sourceE27, max 60W (not included)EffectMax 60WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Glass	Clear glass
Weight1,4 kgDiameter (mm)116Height (mm)204Lamp holderE27Light sourceE27, max 60W (not included)EffectMax 60WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Glass thread (mm)	99 mm
Diameter (mm)116Height (mm)204Lamp holderE27Light sourceE27, max 60W (not included)EffectMax 60WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Glass gasket	Silicone
Height (mm)204Lamp holderE27Light sourceE27, max 60W (not included)EffectMax 60WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Weight	1,4 kg
Lamp holderE27Light sourceE27, max 60W (not included)EffectMax 60WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Diameter (mm)	116
Light sourceE27, max 60W (not included)EffectMax 60WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable glandsBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Height (mm)	204
EffectMax 60WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Lamp holder	E27
Rated voltage230VRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Light source	E27, max 60W (not included)
IP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Effect	Max 60W
Insulation classIIInsulation classIID classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Rated voltage	230V
D classNoIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	IP class	IP54
INSCIK classIK02Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Insulation class	11
Ta-30 - +25InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	D class	No
InstallationCeiling/wallCC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	IK class	IK02
CC measurement (mm)60-66, 70Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Та	-30 - +25
Knock out opening0Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Installation	Ceiling/wall
Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	CC measurement (mm)	60-66, 70
Cable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Knock out opening	0
Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Cable inlet	Bottom inlet
BridgingYesSurface mounted cableNoConnectionMantle screwFamilyOpus	Cable glands	Bottom inlet
Surface mounted cable No   Connection Mantle screw   Family Opus	Cable area, max	Max 2 x 2,5 mm2
Connection Mantle screw   Family Opus	Bridging	Yes
Family Opus	Surface mounted cable	No
	Connection	Mantle screw
Design Duoform	Family	Opus
	Design	Duoform





### Luminaire specific information

The shade is mouth-blown, therefor they are all unique, minor variations may occur.

#### Maintenance

Disconnect the power to the luminaire. Unscrew the glass and clean it. Do not use detergents that contain solvents. Replace light source if necessary. Check the gasket and replace it if necessary. Screw the shade back on.

#### Spare parts

Shade Opus 120 clear glass, Article no.: 1-6184-10 Gasket silicone for thread 99 mm, Article no.: 03542

If the luminaire is modified the person responsible for the modification shall be considered manufacturer. Subject to errors in text. We reserve the right to change the technical specifications (without notice).