

Opus 100/175 Sauna

Opus 100/175 is an elegant cylindrical light fitting in a timeless design with a ceramic base. Suitable for both walls and ceilings in saunas.


EAN / GTIN	7312908240208
E-number	7530441
Article no.	8240-519-10
Type designation	7240
Norwegian El-number	3041074
Finnish S-number	4212251



Specification

Base colourWhite (NCS \$ 1000-N)GlassClear glassGlass thread (mm)84,5 mmGlass gasketSiliconeWeight0,77 kgDiameter (mm)97Height (mm)171Lamp holderE27Light sourceMax 40W ceiling/60W wall (included)EffectMax 40W ceiling/60WRated voltage230VIP classIP44Insulation classIIEnergy classGD classNo	1		
Glass thread (mm) 84,5 mm Glass gasket Silicone Weight 0,77 kg Diameter (mm) 97 Height (mm) 171 Lamp holder E27 Light source Max 40W ceiling/60W wall (included) Effect Max 40W ceiling/60W Rated voltage 230V IP class IP44 Insulation class II Energy class G)		
Glass gasketSiliconeWeight0,77 kgDiameter (mm)97Height (mm)171Lamp holderE27Light sourceMax 40W ceiling/60W wall (included)EffectMax 40W ceiling/60WRated voltage230VIP classIP44Insulation classIIEnergy classG			
Weight 0,77 kg Diameter (mm) 97 Height (mm) 171 Lamp holder E27 Light source Max 40W ceiling/60W wall (included) Effect Max 40W ceiling/60W Rated voltage 230V IP class IP44 Insulation class II Energy class G			
Diameter (mm) 97 Height (mm) 171 Lamp holder E27 Light source Max 40W ceiling/60W wall (included) Effect Max 40W ceiling/60W Rated voltage 230V IP class IP44 Insulation class II Energy class G			
Height (mm) 171 Lamp holder E27 Light source Max 40W ceiling/60W wall (included) Effect Max 40W ceiling/60W Rated voltage 230V IP class IP44 Insulation class II Energy class G			
Lamp holder E27 Light source Max 40W ceiling/60W wall (included) Effect Max 40W ceiling/60W Rated voltage 230V IP class IP44 Insulation class II Energy class G			
Light source Max 40W ceiling/60W wall (included) Effect Max 40W ceiling/60W Rated voltage 230V IP class IP44 Insulation class II Energy class G			
Max 40W ceiling/60W wall (included) Effect Max 40W ceiling/60W Rated voltage 230V IP class IP44 Insulation class II Energy class G			
Rated voltage 230V IP class IP44 Insulation class II Energy class G			
IP class IP44 Insulation class II Energy class G	' wall		
Insulation class II Energy class G			
Energy class G			
D class No			
IK class IK02			
Ta Max +125			
Installation Ceiling/wall			
CC measurement (mm) 60-66, 70			
Knock out opening 0			
Cable inlet Bottom inlet			
Cable glands Bottom inlet			
Cable area, max Max 2 x 2,5 mm2.			
Bridging Yes			
Surface mounted cable No			
Connection Mantle screw			
Family Sauna			
Design Duoform			





Luminaire specific information

Our shades are all unique, minor variations may occur. The luminaire is designed to be installed in ambient temperatures of up to 125 °C. Also approved for steam rooms. Sauna light source, E27, 30W included.

Maintenance

Disconnect the power to the luminaire. Unscrew the glass and clean it. Do not use detergents that contain solvents. Replace light source if necessary. Check the gasket and replace it if necessary. Screw the shade back on.

Spare parts

Shade Opus 100/175 clear glass, Article no.: 1-6182-10 Gasket silkon for thread 84,5 mm, Article no.: 02786-9

If the luminaire is modified the person responsible for the modification shall be considered manufacturer. Subject to errors in text. We reserve the right to change the technical specifications (without notice).