

Ohm Pendant 100/155


A family of porcelain luminaires for walls, ceilings and tables. Designed by Kauppi & Kauppi, the soft curves and restrained silhouette references to both Scandinavian design and ancient Japanese tableware.

EAN / GTIN	7312908321105
E-number	7506565
Article no.	8321-200-10
Type designation	51820/G9

Specification

Base colourWhite (NCS \$ 1000-N)GlassMatt opal glassGlass thread (mm)84,5 mmGlass gasketSiliconeWeight1,27 kgDiameter (mm)98Height (mm)155Lamp holderG9Light sourceMax 20W (not included)EffectMax 20WRated voltage230VIP classIP44 (inside usage)Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhmDesignKauppi & Kauppi	Material	Porcelain
GlassHan open giveGlass gasketSiliconeWeight1,27 kgDiameter (mm)98Height (mm)155Lamp holderG9Light sourceMax 20W (not included)EffectMax 20WRated voltage230VIP classIP44 (inside usage)Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Base colour	White (NCS S 1000-N)
Glass gasketSiliconeWeight1,27 kgDiameter (mm)98Height (mm)155Lamp holderG9Light sourceMax 20W (not included)EffectMax 20WRated voltage230VIP classIP44 (inside usage)Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Glass	Matt opal glass
Weight1,27 kgDiameter (mm)98Height (mm)155Lamp holderG9Light sourceMax 20W (not included)EffectMax 20WRated voltage230VIP classIP44 (inside usage)Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Glass thread (mm)	84,5 mm
Diameter (mm)98Height (mm)155Lamp holderG9Light sourceMax 20W (not included)EffectMax 20WRated voltage230VIP classIP44 (inside usage)Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Glass gasket	Silicone
Height (mm)155Lamp holderG9Light sourceMax 20W (not included)EffectMax 20WRated voltage230VIP classIP44 (inside usage)Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Weight	1,27 kg
Lamp holderG9Light sourceMax 20W (not included)EffectMax 20WRated voltage230VIP classIP44 (inside usage)Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Diameter (mm)	98
Light sourceMax 20W (not included)EffectMax 20WRated voltage230VIP classIP44 (inside usage)Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Height (mm)	155
EffectMax 20WRated voltage230VIP classIP44 (inside usage)Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Lamp holder	G9
Rated voltage230VRated voltage230VIP classIP44 (inside usage)Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Light source	Max 20W (not included)
Instant for the getIP classIP classIP 44 (inside usage)Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Effect	Max 20W
Insulation classIID classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Rated voltage	230V
D classNoIK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	IP class	IP44 (inside usage)
IK classIK02Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Insulation class	11
Ta-30 - +25InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	D class	No
InstallationCeilingKnock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	IK class	IK02
Knock out opening0Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Ta	-30 - +25
Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableNoConnectionTerminal blockFamilyOhm	Installation	Ceiling
Bridging Yes Surface mounted cable No Connection Terminal block Family Ohm	Knock out opening	0
Surface mounted cable No Connection Terminal block Family Ohm	Cable area, max	Max 2 x 2,5 mm2
Connection Terminal block Family Ohm	Bridging	Yes
Family Ohm	Surface mounted cable	No
	Connection	Terminal block
Design Kauppi & Kauppi	Family	Ohm
	Design	Каиррі & Каиррі





Luminaire specific information

Equipped with textile cable (2m) with ceiling rose in porcelain and a terminal on the end. The luminaire is approved for use in areas with IP44 demands, indoors only.

Maintenance

Disconnect the power to the luminiarie. Remove the shade and clean it. Do not use cleaning agents containing solvents. Change the light source if necessary. Check the gasket and change it if necessary. Replace the shade.

Spare parts

Shade Ohm 100/110 matt opal, Article no.: 1-6160-30 Gasket silkon for thread 84,5 mm, Article no.: 02786-9

If the luminaire is modified the person responsible for the modification shall be considered manufacturer. Subject to errors in text. We reserve the right to change the technical specifications (without notice).